

1. The product (unique identification code): TERAFIX COMFORT PLUS

2. Type, line or serial number of the product

Improved cement adhesive with reduced slippage and prolonged bonding time of the TERAFIX, type COMFORT PLUS, class C2TE according to EN 12004: 2007 + A1; 2012. The batch number is indicated on the packaging.

3. Intended use

It is used for bonding ceramic tiles and pavers based on natural and artificial stone, flat tiles and paving strips, facing-bricks and porous, dense and sintered ceramic tiles and pavers in interiors and exteriors.

4. Name, company or registered trade mark and contact address of the manufacturer:

TopTeramo s.r.o.
H# 444
790 64 Vápenná
IČ: 27789969

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article. 12 paragraph 2: Not applicable

6. The system or systems of assessment and verification of constancy of performance of a construction product, as specified in Annex V:

System 3 and reaction to fire in system 4

7. In the case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body no. 1544: QUALIFORM, a.s., Mlaty 672/8, 642 00 Brno, Czech Republic,

Performed a test of the product type in system 3

Released a report on the outcome of initial type testing of the product: 28300/01-PZ-16

The notified body no. 1391: PAVUS, a.s., Prosecká 412/74, 190 00 Praha - Prosek, Czech Republic,

Conducted product testing - reaction to fire

Issued the Protocol on the classification of the reaction to fire PK-01-16-009-C-0

8. In the case of the declaration of performance concerning a construction product for which an ETA had been issued: Not applicable

9. Properties listed in the DoP

Initial tensile adhesion strength	according to DIN EN 1348 8.2)	[MPa]	≥ 1,0
Tensile adhesion strength after immersion in water	according to DIN EN 1348 8.3)	[MPa]	≥ 1,0
Tensile adhesion strength after freeze-thaw cycles	according to DIN EN 1348 8.5)	[MPa]	≥ 1,0
Tensile adhesion strength after heat ageing	according to DIN EN 1348 8.4)	[MPa]	≥ 1,0
Open time - tensile adhesion strength after 30 minutes	according to DIN EN 1346	[MPa]	≥ 0,5
Slippage	(EN 1308: 1996)	mm	< 0,5
Release of dangerous substances	see Safety Data Sheet		
Reaction to fire	(EN 13501-1)	class	A1

10. Product characteristics mentioned in paragraphs 1 and 2 of this statement are consistent with the characteristics listed in the table in paragraph 9. This declaration of performance is issued under the sole responsibility of the manufacturer referred to in paragraph 4.

Signed for and on behalf of the manufacturer:

Ing. Zdeněk Rýznar
Production Manager

Effective date: March 31, 2016

Prepared on March 30, 2016 by : Ing. Milan Ševčík

signature:

Supersedes all previous versions

Approved on March 31, 2016 by : Ing. Zdeněk Rýznar

signature: